



Phase Equilibrium Modeling for the DME Enhanced Water-flooding

Tsanas, Christos; Stenby, Erling H.; Yan, Wei

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Tsanas, C., Stenby, E. H., & Yan, W. (2017). *Phase Equilibrium Modeling for the DME Enhanced Water-flooding*. Abstract from Danish Hydrocarbon Research and Technology Centre Technology Conference 2017, Lyngby, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Danish Hydrocarbon Research and Technology Centre Technology Conference 2017

Phase Equilibrium Modeling for the DME Enhanced Water-flooding

Christos Tsanas, Erling H. Stenby, Wei Yan

Center for Energy Resources Engineering (CERE), Department of Chemistry, Technical University of Denmark, 2800 Kongens Lyngby, Denmark, email: weya@kemi.dtu.dk

Dimethyl ether (DME) has recently emerged as a novel-solvent in water-flooding enhanced oil recovery (EOR), because it can be dissolved in both the oil and the water/brine phase. DME dissolves preferentially in the oil phase (first contact miscible), causing swelling and reducing the viscosity of the oil, thus improving its mobility. Dynamic modeling and DME enhanced water flood simulations require accurate phase description. The purpose of this work is to provide satisfactory modeling of the DME partitioning between the oil and the water/brine phases. Two models were used: the Cubic Plus Association (CPA) equation of state (EoS) and cubic EoS (CEoS) with Huron-Vidal (HV) mixing rules. Parameters for CPA and CEoS-HV were regressed for binary systems of DME with water, several HCs, carbon dioxide and nitrogen. Overall the results were satisfactory. Finally, predictions with CPA were made in ternary mixtures of DME/water/HC. DME/water required temperature dependent parameters to capture sufficiently the experimental data, whereas the rest of the systems needed only one temperature independent parameter. Analysis of the modeling results can provide beneficial information to the planning of core flood experiments.

Category: Advanced Water Flooding 1 – Development of Ekofisk



AARHUS UNIVERSITY



UNIVERSITY OF
COPENHAGEN

Technical
University of
Denmark



GEUS



AALBORG UNIVERSITY
DENMARK